

# **CHEMTROL 405**

## **APPLICATION**

POWDERED INHIBITED ACID CLEANER FOR HEAVY SCALE REMOVAL AND AS BLEACH TO RESTORE METAL COLORS AFTER ABRASIVE FINISHING OPERATIONS

#### DESCRIPTION

DRY WHITE FREE FLOWING DRY ACID SALT CONTAINING DRY FORM OF SULFURIC ACID IN COMBINATION WITH DETERGENTS AND WETTERS. NON-FLAMMABLE. PH OF 1% IN WATER SOLUTION = 1.9.

## **HANDLING**

<u>DANGER CONTAINS ACID</u> LIBERATES SULPHURIC ACID WHEN CONTACTED BY WATER. CAN CAUSE BURNS OR SKIN IRRITATION. USE RUBBER GLOVES AND EYE PROTECTION WHEN HANDLING.

# **FIRST AID**

IN CASE OF CONTACT, IMMEDIATELY FLUSH SKIN OR EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. FOR EYES, GET PROMPT MEDICAL ATTENTION. (RED LABEL)

#### STORAGE

STORE IN DRY AREA IN CLOSED CONTAINER.

# **DISPOSAL**

MAY REQUIRE ALKALINE NEUTRALIZATION TO MEET LOCAL CODES. SETTLE SOLIDS IF NECESSARY.

### **PACKAGING**

100 LB. NET POLYETHYLENE LINED NON-RETURNABLE FIBRE DRUMS.

