

Chemtrol 559NSS

Industrial Spray Cleaner

Chemtrol 559NSS is a concentrated liquid multi-metal cleaner designed for use in spray wash equipment.

Chemtrol 559NSS effectively cleans fabrication soils and provides temporary rust protection on ferrous metals.

Chemtrol 559NSS is a non-silicated, free rinsing in-process cleaner for use prior to painting.

Chemtrol 559NSS is low foaming and splits free oils for more effective skimming or coalescing. This will extend bath life and reduce waste and maintenance.

Uses:

Spray Washers

Use at 2 to 5% by volume depending on soils and frequency of application with an operating temperature range of 80° to 160°.

Power Washers

Use at 1 to 4% by volume depending on soils and frequency of application with an operating temperature range of 80° to 160°.

Physical Properties

Appearance	Clear liquid	Odor	Mild
Biodegradable	Yes	pH @ 1%	~10.0
Specific Gravity	1.1	Flash Point	None
Emulsification	Rapid	Wetting Ability	Excellent
Foaming	Controlled/Low	Rinsing	Excellent

Environmental

No health or safety hazards exists when Chemtrol 559NSS is used, stored, and disposed of in accordance with instructions on the Material Safety Data Sheet for this product.



**Precision
Finishing Inc.**